

TRYON

STYLE AND PERFORMANCE

New brand signature, TRYON is available in 3 versions : safety spectacles, OTG and prescription spectacles. Ultra-wrap-around, sporty design, co-injected FLEX 160° temples, adjustable and non-slip bridge, PLATINUM® coating... TRYON perfectly combines style, innovation and absolute protection.

 PLATINUM®



26g



TRYOPSI



TRYOPSF



TRYOCSP



TRYOFASH


















RUSHKITS (option)
Strap

- + WRAP-AROUND FRAME
- +  PLATINUM® COATING ()
- EXCEPT FLASH VERSION
- + CO-INJECTED PC/TPR TEMPLES
- + NON-SLIP ADJUSTABLE BRIDGE
- + FLEX 160° TEMPLES

bollé
SAFETY

TRYON

STYLE AND PERFORMANCE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
TRYON	 Clear	TRYOPSI	2C-1,2  1 FT KN €€	 EN166 FT €€	Anti-scratch/Anti-fog 
	 bCSP	TRYOCSP	5-1,4  1 FT KN €€	 EN166 FT €€	Anti-scratch/Anti-fog 
	 Smoke	TRYOPSF	5-3,1  1 FT KN €€	 EN166 FT €€	Anti-scratch/Anti-fog 
	 Blue flash	TRYOFLASH	5-3,1  1 FT €€	 EN166 FT €€	Anti-scratch/Anti-fog (inside)
	Strap only (option)	RUSHKITS	-	-	-

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:


F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

€€ European standard  Manufacturer name

TECHNOLOGIES

bCSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

PLATINUM


The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

	TRYOPSI	TRYOPSF	TRYOCSP	TRYOFLASH	RUSHKITS
Individual plastic bag	3660740008260	3660740008277	3660740008284	3660740008437	3660740007546
10 safety spectacles per inner box	3660740108267	3660740108274	3660740108281	3660740108434	3660740107543
240 safety spectacles per outer pack	3660740208264	3660740208271	3660740208288	3660740208431	3660740207540

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	-
TEMPLES	PC + TPR
STRAP	Nylon/15mm/Adjustable
SPARE LENSES	No



Non-contractual pictures

18/04/2017

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY