

IRI-S DIOPTER

IRI-S, A SINGLE MODEL FOR THOUSANDS OF FACES

IRI-S, the first universal safety spectacle that fits perfectly to every face. Featuring a B-Flex nose bridge, fully adjustable in height, depth and width. An ultra-light weight frame with pivoting ergonomic temples, fitting precisely to all face shapes and features five reading area diopter versions.



-  Clear Lens +1.0 : 1671001
-  Clear Lens +1.5 : 1671002
-  Clear Lens +2.0 : 1671003
-  Clear Lens +2.5 : 1671004
-  Clear Lens +3.0 : 1671005



Multi adjustable
B-flex nose bridge
allows tilt and
width adjustability



Tilt adjustable,
co-moulded
temple arms for
customised
secure fit













29 g

- + 1 MODEL - 1 SIZE**
- + PIVOTING, NON SLIP & ERGONOMIC TEMPLES**
- + 5 READING AREA VERSIONS**
- + B FLEX NOSE BRIDGE**

bolle
SAFETY

IRI-S DIOPTER

IRI-S, A SINGLE MODEL FOR THOUSANDS OF FACES

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
IRI-S DIOPTER	 Clear Lens +1.0	1671001	IO & 	AS/NZS 1337.1	Anti-scratch/Anti-fog
	 Clear Lens +1.5	1671002	IO & 	AS/NZS 1337.1	Anti-scratch/Anti-fog
	 Clear Lens +2.0	1671003	IO & 	AS/NZS 1337.1	Anti-scratch/Anti-fog
	 Clear Lens +2.5	1671004	IO & 	AS/NZS 1337.1	Anti-scratch/Anti-fog
	 Clear Lens +3.0	1671005	IO & 	AS/NZS 1337.1	Anti-scratch/Anti-fog

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses
-  Manufacturer name

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100%.

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory
- Dental

MAIN MARKETS

- Manufacturing
- Local government and councils
- Utilities: power, gas, water and roads
- Medical and dental
- Transport
- Mining
- Construction
- Dental

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **BOLLÉ CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 10
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz